


DOT **9234**  
 DOT **9238**

DOT **LED**



1100 LM  
 CREE XM-L  
 LED engine



146mm

▶ 140mm dia. hole ◀  
 ▶ 155mm dia. o/a ◀

MODELS



White Ceiling Plate A930/01 fitted to downlight as standard.

Total Energy Consumption P <sub>t</sub> (W)		
3000K – Colour 830		10.4W (72.4Lm/W)
4000K – Colour 840		10.5W (79.6Lm/W)
Weights	Luminaire Body	1000 gms
	Remote Driver	190 gms
IEC 60598.1.2		Complies
AS/NZS60598.1.2		Complies
IP Rating		Refer Accessory
Dimming Option Available		
- Analogue dimming 0-10 volt		AD
- DALI dimming		DALI
- DSI dimming (Digital Serial Interface)		DD
Weights	Luminaire Body	1000 gms
	Remote Driver	145 gms

**AXLOCK ACCESSORIES** Fitted to downlight after installation.  
 Accessory trims available White /01 or Silver /55.

A930		Round Ceiling Plate IP20	A938		Square Ceiling Plate IP20
A931-DL		Round – Soft Diffusion Lens IP54	A932-DL		Square – Soft Diffusion Lens IP54
A933		Round Washlight Lens IP54	A934		Square Washlight Lens IP54
A937-FG		Round Flush Glass IP54	A937-DG		Round Dropped Glass IP20

ORDERING CODE FORMAT

Example: DOT 9234 /30 /DALI /A930				
Model Number	(9234 or 9238)			
LED engine colour	(/30-830 or /40-840)			
Dimming option if required	(/AD, /DALI or /DD)			
Accessory Code				

DOT **9234**  
DOT **9238**



1100 LM  
CREE XM-L  
LED engine

